

SNOW REMOVAL DEVICE

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to manually operated shoveling and plowing devices, and more particularly to a manually operated shoveling device capable of scraping and gathering, lifting, and dumping large quantities of a granular or other material such as snow quickly and with a minimal amount of physical exertion and strain on the operator.

2. Preliminary Discussion

Well known is the fact that shoveling snow with a conventional shovel is very labor intensive and places considerable stress on the shoveler's body. A Journal of the American Medical Association study found that people who rarely exercise are up to 30 times more likely to have a heart attack when suddenly undertaking a strenuous activity such as snow shoveling. The physical labor of shoveling quickly drives up one's blood pressure and heart rate, particularly in those people who are out of shape and not used to regular physical exertion. Cold weather only adds to the stress, because the cold tends to constrict blood vessels, not only at the surface of the body, but generally, while at the same time extra blood is needed flowing to the heart to compensate for the workout. The main reason for the initiation of such injury during shoveling is that the amount of stress exerted is usually underestimated by the shoveler. Researchers in Michigan recently monitored the vital statistics of 10 healthy men in their 20's and 30's, including heart rate, as they ran on a treadmill to the point of exhaustion. Shortly thereafter, the same group was monitored as they shoveled heavy, wet snow for about ten minutes. The results showed that the men's heart rates during or after shoveling were at least as high or higher than their heart rates on the treadmill.

In addition to risk of heart attacks, the stress of shoveling can lead to other

serious physical injuries, the most serious of which are usually back injuries. In fact, although one might think that older individuals are more at risk of suffering a back injury while shoveling, shovelers between the ages of 20 and 50 are generally more likely to suffer a back injury than older individuals, because older individuals are more likely to
5 be aware they are out of condition, and therefore more likely to “take it easy” so to speak. The risk of suffering a back injury is also more likely in the morning because the tissue around the shoveler’s spine is not warmed up or loose. Many slipped discs also occur in the morning when there is increased fluid pressure in the cerebrospinal fluid which increased pressure is exerted upon and internally of the disc. Resulting “over
10 inflation” of the disc increases the likelihood of the top and bottom of the disc moving laterally relative to each other.

Use of proper lifting technique and shoveling at a slower, steady pace can greatly reduce the risk of injury while shoveling. For example, in lifting a loaded shovel,
15 the shoveler should bend his or her knees while lifting with the legs and not with the back. Excessive twisting, bending or throwing snow over the shoulder should be avoided to prevent spinal injury, as the spine can tolerate almost any almost any other movement more easily than twisting. Stepping in the direction the snow is being thrown will also prevent some twisting. In addition, smaller shovel loads should be lifted rather
20 than heavy or full shovel loads. Frequent breaks should be taken, and the lower back should be extended either by walking around or doing extension exercises by placing one’s hands on the back of his or her hips and bending forward slightly for several seconds, and then bending backward also for several seconds.

25 Despite such precautions, which are not taken by most or even many shovelers, muscle fatigue, low back strain, vertebral disc damage, and even spinal fractures occur during the winter season, caused either by excessive stress to spinal structures and others by slip and fall accidents. Thus, since most of such shoveling injuries occur as a result of lifting and throwing or dumping loads of snow, an even better solution to
30 preventing injuries to one’s back or other muscles is to push the snow to the grassy

area beside a sidewalk or driveway instead of lifting and throwing it. Some back injuries occur due to the fact that the shaft of the shovel is too short, which causes the back to bend more to lift the load, or by using a shovel with a shaft that is too long the resulting excessive leverage effectively making the weight at the end relatively heavier. In

5 addition, several shovels today have curved shafts or handles which enable the user to keep his or her back straight or straighter while lifting and reduce the amount of bending required during use. Such curved shaft shovels, however, in general place even more stress on the body if the snow has to be lifted up to or over a pile of previously collected snow or other barrier. Other snow handlers choose to do away with manual shoveling
10 altogether, and instead use a snow blower. However, while snow blowers do in fact eliminate lifting of snow, they are quite expensive to purchase and maintain, and can be dangerous if not used or cleaned correctly. In fact, hand injuries caused by cleaning out a snow blower by hand are quite common, despite repeated warnings. Snow blowers, furthermore, are inefficient with heavy wet snow which is also the most difficult
15 to move by means of a shovel.

As discussed in more detail in reviewing the prior art references below, in an attempt to reduce the exertion and amount of lifting required, the principle of leverage has been adopted for use in various shovel arrangements. In most cases, the shovel
20 shaft or handle acts as an extended lever which is pivoted against a fulcrum attachment to lift a load, in this case a shovel blade loaded with snow. Essentially, by applying a downward lift force on the lever, the amount of work required to lift the loaded shovel is reduced. The human body or more specifically the arm is itself essentially a third class lever, i.e. the fulcrum point is at the end of the lever and the exertion of force is between
25 the fulcrum point and the point at which force is to be exerted. However, third class levers offer no advantage to gravity in terms of power, since they require more force to move against the force of gravity than the weight to be moved. For example, to lift twenty pounds with one's hand, the arm muscles actually put about two hundred pounds of force on the forearm, so that the force that goes into the body is
30 approximately ten times the force being lifted. Therefore, while third class levers such

as the human body or more particularly the arms are good for mobility and speed, they are very inefficient in terms of lifting against the force of gravity and/or in terms of energy. In addition, the load is supported by an articulated but only partially flexible column represented by the spinal column maintained in alignment by multiple individual

5 muscles and tendons which must operate in complete coordination to prevent misarticulation, which is a primary reason why back injuries often occur while lifting heavy items. The entire weight, whatever it is furthermore in shoveling, is exerted upon the spinal column with a significant twisting moment made greater by the length of the shovel handle. Second class levers, an example of which is a wheelbarrow, where the
10 weight of the load is exerted between the fulcrum point and the point of exertion of lifting force and thus attains a mechanical advantage, offer some additional mechanical advantage, but the load is still essentially placed so that to get any such mechanical advantage, one is still lifting up against the force of gravity. In a wheelbarrow, the load is situated essentially behind or right over the fulcrum, and one must lift up against
15 gravity to move the load. In a first class lever, however, such as a shovel having a fulcrum type attachment, one pushes down in the same direction as the force of gravity on the handle, which is easier than lifting against gravity, causing the other loaded end to be lifted upwardly. The longer the lever on the down side of the fulcrum in comparison to the load side, the less effective force is required to lift the load.
20 Approximately thirty-three pounds of down force on one side of the lever, which force is enhanced by the force of gravity, is translated into a hundred pounds of up force on the opposite side of the lever if the downward force application side is three times as long as the lift side.

25 The present inventor has conceived of a novel snow shoveling device wherein all of the lift required in lifting a load of snow comes from a unique first class lever arrangement in which the handle of the shovel serves as the fulcrum support. As a result, little or no physical exertion other than pushing the shoveling device across the area to be cleaned and pushing downwardly on the lever mechanism with one's body
30 weight, preferably by the use of the large leg muscles rather than the relatively smaller

arm muscles, is required. In addition, once the load is lifted, such load is easily released from the shoveling blade again with only minimal physical strain or exertion when compared to the large strain on the heart and muscles in shoveling using a regular hand shovel. Even more important in the present invention, however, is that

5 instead of the weight of the snow or other congealed precipitation being supported during lifting by the articulated cervical column of the shoveler of the snow the weight of the snow is supported by the much more durable and damage resistant handle of the shovel which rests upon the underlying surface from which the snow is being removed during lifting and the downward force is applied as indicated to the leveraged shovel

10 blade not by the relatively weak muscles of the arms, but by the considerably more powerful muscles of the legs or one leg, further removing stress from the spine, since the legs of the human torso are articulated into the hips below the spine. The only stress to the spine, therefore, is the relatively low stress of maintaining the shovel handle upright upon the surface from which snow is being removed and even this stress

15 comprises only a relatively low sidewise force effective to maintain the shovel handle essentially upright. Furthermore, even this low can be partially alleviated by providing multiple point, such as four point, bottom contact of the shovel handle with ground surface. The actual dumping of snow from the shovel blade once it is elevated can be effected in several different ways, as will be explained, such as overbalancing of the

20 shovel blade and the use of push rod means to rotate the blade.

3. Description of Related Art

As indicated above, various arrangements are known in the prior art which are designed to lessen the amount of work and physical exertion involved in lifting a load

25 using a shovel. Many of these arrangements involve a use of fulcrumed load lifting. However, none of such arrangements of which the present inventor is aware involve the use of a handle which supports a lifting fulcrum against the support of the ground.

One common device is the addition of an auxiliary handle to a shovel normally

30 having a single gripping area on the upper end of the regular handle. For example,

U.S. PAT. NO. 584,827 issued to B.F. McIndoo on June 22, 1897, entitled "Shovel," is an early example of a shovel having an auxiliary handle pivotably connected to the lower end of the regular handle. To lift a load, the auxiliary handle is swung forwardly where it is held by a pawl and rack arrangement. When the load is ready to be pitched
5 off the shovel blade, the pawl is disengaged from the rack and the auxiliary handle is allowed to naturally swing backwards toward the other upper end of the regular handle.

In U.S PAT. NO. 4,198,090 issued to D. Gutman on April 15, 1980, also entitled "Shovel," teaches a shovel having an adjustable lever situated partway along the handle portion of the shovel and a secondary handle member connected to the upper
10 handle portion of the shovel. Gutman also utilizes a lever mechanism to aid in initially lifting a load on the scoop member; however, considerable lifting and strain is still required to support and dump the load.

As another example, in U.S. PAT. NO. 4,881,332 issued to G.L. Evertsen on
15 November 21, 1989, entitled "Shovel Lifting Aid," a shovel handle having a swivelable bar connected thereto and arranged so that when the user's foot is placed on the bar and the shovel blade is filled with a load, the load is lifted by pulling rearwardly on the handle until the load is essentially balanced on the lifting aid. Once lifted, the handle may be pivoted to the side to dump the load. A wheel arrangement as part of the lifting
20 aid is also contemplated. In U.S. PAT. NO. 5,440,828 issued to R.C. Simpson on August 15, 1995, entitled "Manual Snow Removal Tool," a shovel in which the handle is pivotable to either side within a range of angular positions with respect to the blade is shown, which allows the shovel to be used both conventionally to scoop and then lift and throw a load of snow, or to windrow the snow when the handle is set at an oblique
25 angle with respect to the blade.

A large number of shovels having fulcrum or pivot attachments are also well known. U.S. PAT. NO. 738,057 issued to E.B. O'Connor on September 1, 1903, entitled "Shovel Attachment," discloses a fulcrum type attachment for a shovel that acts
30 as a rocker on which the shovel rests and rocks as the shovel is moved forward or

rearward. Rocking of the shovel on the fulcrum eliminates the need to stoop to fill the shovel.

U.S. PAT. NO. 2,734,291 issued to C.C. Lasker on February 14, 1956, entitled
5 "Manually Operated Snow Removal Tool," discloses a scoop or shovel having a pair of curved combination rocker and skids connected to the back of the shovel blade. In use the shovel blade is pushed over the surface to be cleaned, and then is tilted upwardly by pushing down on the handle so that the shovel blade is pivoted off the ground and is supported on the rocker and skids. The tool is then pushed to a dumping area on the
10 skids and pivoted forwardly onto the front edge of the blade so that the snow will simply slide off the blade. While Lasker eliminates lifting of the loaded shovel, it may be difficult to dump the snow if more than a few inches has fallen since the blade is always at more or less ground level.

15 U.S. PAT. NO. 2,769,612 issued to C. Weisheit on November 6, 1956, entitled "Shovel With Lifting Means," discloses a shovel having attached both an auxiliary handle and a fulcrum or lever device. The fulcrum or lever is connected to the bottom side of the shovel handle via a plate member, while the pivotable handle is connected to the upper side of the shovel handle. A spring arrangement is also used to continually
20 urge the shovel blade into contact with the ground. Pulling upwardly on auxiliary handle and pushing downwardly on the regular handle causes the shovel blade to pivot upwardly so it is balanced on the fulcrum or lever. Such system aids in the initial lifting process but still requires the user to support the entire weight of the load of snow prior to dumping.

25

U.S. PAT. NO. 3,035,816 issued to M.A. Conant on May 22, 1962, entitled "Foot Lever for a Hand Shovel," discloses another lever device which when downward pressure is placed on the foot pedal, the lever rocks so that the loaded shovel blade is forced upwardly. If enough downward force is placed on the foot lever, the snow or
30 load will continue moving in an upward direction and may then be easily deflected to the

side by turning the shovel handle or blade.

U.S. PAT. NO. 3,343,807 issued to A.L. Moraski on September 26, 1967,
entitled "Shovel," discloses an arrangement similar to that found in Lasker but with a
5 pair of arcuate legs forming a fulcrum point for pivoting the shovel blade upwardly. In
addition, a pair of roller wheels are provided to facilitate forward or rearward movement
of the shovel.

U.S. PAT. NO. 3,748,761 issued to C.H. Chetwynde on July 31, 1973, entitled
10 "Snow Handling Device," discloses a shoveling device having a wheeled carriage
structure with an upwardly telescoping jack and front link having sleeves or couplings
for receiving a shovel handle so that it may be rotated axially within a certain range.
The jack acts as a fulcrum for lifting snow piled in the scoop by pressing downwardly on
the other end of the shovel handle. The handle is then turned axially to dump the snow,
15 which dumping height may be adjusted by changing the length of the telescoping jack.

U.S. PAT. NO. 4,130,953 issued to A.T. Bruno on December 26, 1978, entitled
"Snow Jack," discloses another scoop or shovel pivotably mounted to a lever arm
mounted on a pedestal connected to a sled or base. The scoop is pivotable in either a
20 horizontal or vertical plane on the pedestal, while a release catch extending along the
lever arm to the handle is used to release the scoop and dump the snow. After snow
accumulates in the scoop the handle portion of the lever arm is pushed downwardly so
that the scoop is lifted off the ground. The release is then actuated, causing the scoop
to pivot downwardly on a hinge and release snow in the scoop.

25

U.S. PAT. NO. 5,074,064 issued to J.G. Nickels on December 24, 1991, entitled
"Snow Shovel," discloses a shovel wherein a snow ejection plate forms the bottom wall
of the shovel which when swung from a prone to an upright position by pulling upwardly
on a hand grip forces snow out of or off of the shovel blade.

30

In U.S. PAT. NO. 5,569,651 issued to A. Vroegindewey on September 23, 1997, entitled "Shovel With Lift Aid Attachment," a cambered foot pedal attachment is pivotably connected extending rearwardly from the lower end of the handle shaft which when stepped on by the user urges the shovel blade to be raised upwardly by lever
5 action. Also, an auxiliary handle on the forward end of the lever is used to help throw snow off of the shovel blade. At some point, however, the full weight of snow still must be supported by the user.

In U.S. PAT. NO. 5,732,933 issued to F.K. Champi on March 31, 1998, entitled
10 "Lifting Implement," another cambered foot actuated lifting aid attachment for a conventional snow shovel is disclosed. Champi is conceptually similar to the Vroegindewey lifting aid, although it does not include an auxiliary handle, with the lifting aid pivotably connected to the shovel handle by a hinge clamp having a spring therein. A hook is also provided to hold the attachment close to the shovel handle when not in
15 use.

U.S. PAT. NO. 6,086,049 issued to D.A. Sheils on July 11, 2000, entitled "Mechanical Assistance Mechanism for Shovels," discloses another lever-type ground engaging rod connected to a shovel shaft near the shovel blade. The Sheils shovel is
20 also pivotable to the side while being supported on the rod to facilitate dumping of the load.

U.S. PAT. NO. 6,203,081 issued to E.B. Kegan, Sr. on March 20, 2001, entitled "Easy Lift Levered Shovel," discloses another shovel having a lever attachment
25 including a spring arrangement for automatically pivoting the lever legs so that they are adjacent to the shovel handle shaft when there is no load on the shovel handle. Dumping of the snow or load is accomplished by lifting the shovel handle and flinging the snow to the side in the usual manner.

30 U.S. PAT. NO. 6,485,076 issued to W. N. Chang on November 26, 2002, entitled

"Versatile Attachment for Shovel," discloses a pivotable angled rod that may be used both as a handle and a foot engaged lifting lever. The Chang attachment may also slide along the ground to aid in transporting snow to a suitable dumping area. Structurally, such arrangement is different from the present invention, however.

5

Combination shovels and pusher arrangements or plows are also known in the prior art. For example, U.S. PAT. NO. 2,239,297 issued to S.E. Allen et al. on April 22, 1941, entitled "Snow Shovel," discloses a device that may be used either as a shovel or plow-type device by adjusting the angle of the handle in relation to the shovel blade. A
10 wing-nut is used to secure the blade and handle at the desired angle.

U.S. PAT. NO. 4,531,713 issued to F.H. Balboni on July 30, 1985, entitled "Snow Removal Implement," discloses an implement having a wide rectangular blade, a U-shaped handle, and a pivot or fulcrum member, designed to be pushed across a snow-
15 filled area, with the blade being pivotable upwardly by applying a downward force on the handle, causing snow to be flipped or tossed off the blade. No means for pivoting or releasing the blade after it has been moved to a raised position is shown, nor is a foot lever used to aid in raising the blade off the ground.

20 U.S. DES. PAT. 275,928 issued to D.R. LoPresti on October 16, 1984, entitled "Levered Shovel Unit," discloses an ornamental design for another shovel having a lever or fulcrum arrangement similar to those described above.

Push-type wheeled snow shovels or scoops are also commonly found in the prior
25 art. U.S. PAT. NO. 3,043,033 issued to H.O. Ingram et al. on July 10, 1962, entitled "Utility Scoop," discloses an adjustable wheeled manual scoop device having a releasable scoop adjusting assembly having a toothed rack portion and a releasable spring locking arrangement that is actuated by a lever situated near the handle of the scoop. When the lever is pressed a detent is released from the toothed rack, and the
30 angle of the scoop in relation to the handle and wheel assembly can be adjusted to

facilitate scooping, carrying and dumping of debris.

U.S. PAT. NO. 3,121,963 issued to C.W. Nolan on February 25, 1964, entitled "Shoveling Device," discloses another wheeled shovel having an independently
5 pivotable subframe including a snow scoop. After the scoop is loaded with snow, it is pivoted upwardly to a horizontal position and is held by a latch member. A chain connected to the rear wall section of the scoop is then pulled, causing such wall section to retract and allowing the load of snow to essentially drop out of the scoop at a
10 dumping location. A counterweight is provided to minimize the physical exertion in pivoting the loaded scoop. The angle of the handle in relation to the scoop makes it impractical or difficult to advance the Nolan device forward along an elongated surface such as the width of a driveway or the like.

U.S. PAT. NO. 3,923,331 issued to A.A. Hollnagel on December 2, 1975, entitled
15 "Snow Scoop," discloses a bucket-type snow scoop designed to be pushed across the ground on a convex ground engaging surface on the bottom side of the scoop as well as runners on a curved frame structure. The scoop is pivotally connected to the frame via a pair of mounting arms. After it is loaded with snow, the bucket is pivoted upwardly by pressing downwardly on the frame handles. A latch may then be released to allow
20 the bucket to pivot forwardly to a dumping position.

U.S. PAT. NO. 3,125,951 issued to A.W. Huerth on November 21, 1978, entitled "Snow Removal Device," discloses another snow scoop or pusher wherein a main body member is connected to a shovel blade portion having raised side walls, plus a handle
25 means. Snow is piled up in the device by pushing it forwardly along the ground with the handle, while the snow is removed from the blade by rapidly decelerating the blade so that the snow is thrown forward. The Huerth device is thus an example of a device designed especially for using accumulated momentum along a surface to propel snow to a specific resting location on such surface.

U.S. PAT. NO. 5,018,282 issued to K.Y. Hong on May 28, 1991, entitled "Mechanical Shovel," discloses a wheeled shovel or snow scoop also having a lever mechanism for emptying the scoop. When downward foot pressure is applied to a bight connected to the lever arm, the scoop slants rearwardly on a pair of gudgeon pins
5 secured in slots on the chassis, and snow is moved to the rear of the scoop. Snow is dumped from the scoop when further pressure is applied to the lever, so that the scoop is angled upwardly and forwardly.

U.S. PAT. NO. 5,271,169 issued to K.J. Konsztowicz on December 21, 1993,
10 entitled "Snow Shovel/Pusher," discloses a combination/convertible snow shovel and plow having a snow pushing blade having a curled-under end so that the blade does not dig into the surface being cleared, which may be a rough or loose stone surface. A handle assembly for pushing the blade on a pair of ski-like runners is provided. No means for lifting or more easily dumping snow from the blade is shown.

15

U.S. PAT. NO. 5,511,327 issued to M.G. Jurkowski et al. on April 30, 1996, entitled "Wheeled Snow Shovelling Device," discloses a cart-like structure for holding a snow shovel or plow having a large centrally located wheel. The cart may be used as a pivot device to lift the shovel blade, and the cart may be tilted on the large wheel to the
20 side to dump snow on an area adjacent to the area to be cleaned. However, Jurkowski indicates that such shoveling device is effective only in rather light snow accumulations of up to approximately 3 inches.

U.S. PAT. NO. 5,918,921 issued to V. Samuelson on July 6, 1999, entitled
25 "Levered Shovel for Moving Snow," discloses a shovel having a wheel assembly connected to approximately the center of the handle shaft of a shovel, which wheel acts as a fulcrum for the shovel.

U.S. PAT. NO. 5,984,393 issued to R.H. Washington on November 16, 1999,
30 entitled "Shovel With Pivoting Head," discloses a shovel and handle assembly wherein

the shovel and handle shaft are joined together by a pivot joint so that the shovel head can rotate around a longitudinal axis with respect to the handle shaft in either a clockwise or counterclockwise direction. Such shovel design reduces the stress caused by the act of turning or twisting and dumping the contents of the shovel, rather than bending and lifting the load. No aid for lifting the load is provided, however, so that a significant amount of bending and lifting is still required.

U.S. PAT. NO. 6,053,548 issued to L.G. Bowles, Jr. on April 25, 2000, entitled "Manually-Operable Combination Shovel and Plow for Snow and Other Material," discloses a shovel wherein the shovel blade is positionable at various fixed angles with respect to the handle. A male and female joint member securable together by pins connects the shovel blade and handle so that the blade may be placed at an angle which is convenient for plowing, rather than shoveling. A toothed and notched opening is provided in the male joint member which allows the blade to be secured at one of three angles or positions with respect to the handle, where it is held by a spring arrangement. When the handle is pulled back or rearwardly, the pins disengage so that the angle of the shovel blade can be adjusted. An auxiliary handle bar is also provided on the main handle to facilitate plowing, and in addition a wheel assembly may be added to the shovel to make plowing even easier.

U.S. PAT. NO. 6,457,757 issued to J.D. Hendrick on October 1, 2002, entitled "Snow Shoveling Apparatus With Handle and Blade Adjustable During Movement of Apparatus," discloses a wheeled shovel wherein the angle of the handle and the blade are adjustable on notched mounting plates. Handle angle and blade angle adjustment levers are also provided so that the settings can be changed during use of the shovel. No additional means for lifting or dumping the snow are disclosed.

While there are obviously, therefore, a large number of shovels having a variety of lifting or dumping aids connectable thereto, each of which is useful for its own purposes, the present inventor's shoveling tool according to this invention substantially

departs from the conventional concepts and designs of the prior art, and in doing so provides an apparatus wherein strain and exertion from both lifting and dumping a heavy load of snow is essentially eliminated. Therefore, since none of the prior art arrangements provides a snow lifting and dumping arrangement in accordance with the

5 teachings of the present inventor's device, it can be appreciated that there exists a need for such a device which is both significantly less expensive than a snow blower, but also is more easily used and safer to use from a physiological standpoint than a conventional snow shovel. In this regard, therefore, the present invention substantially fulfills a significant existing need.

OBJECTS OF THE INVENTION

It is therefore a primary object of the invention to provide a manually operable snow removal device that eliminates much of both the indirect and direct muscular
5 exertion and strain associated with conventional shoveling devices.

It is a further object of the present invention to provide a snow removal device that may be used to easily push or plow quantities of snow on a surface onto a snow
10 pusher blade and then to lift such snow and deposit in a desired location.

It is a still further object of the present invention to provide a shoveling device having a foot activated lever mechanism which eliminates much of the strain and stress associated with lifting a conventional loaded shovel blade.

15 It is a still further object of the present invention to provide a shoveling device wherein snow may be lifted using such shoveling device, and then such snow may be dumped or released from the shovel blade without any further significant physical exertion by the user.

20 It is a still further object of the invention to provide a shoveling device in which the material being shoveled may be either initially plowed or shoveled to a small height and then after the lower portion of the handle is placed on the ground lifted without significant arm lifting exertion to a height suitable to deposit it in a disposal area.

25 It is a still further object of the invention to provide a snow removal shovel-type device having an extended shovel handle having a lower end adapted for resting upon the ground or other surface to support a load of snow while the snow is lifted by foot pressure upon a lever means upon the shovel prior to dumping.

30 It is a still further object of the invention to provide a snow removal and transport

device having a handle with an indirectly attached shovel blade adapted for passage across a ground or other support surface on a ground passage facilitating means plus a surface stabilization surface upon which the shovel device is supported as the load is lifted by a shovel blade and deposited in a disposal area.

5

It is a still further object of the invention to provide a snow removal device which essentially eliminates arm lifting exertion and substitutes therefore leg depression in a semi-stepping motion to elevate the snow prior to depositing it in a snow disposal area.

10 It is a still further object of the invention to provide a snow removal apparatus which supports gathered snow on a ground engaging solid support while transferring the snow from the device to a snow deposite area by foot manipulation.

It is a still further object of the invention to provide a hand snow removal device
15 which substitutes a rigid support means for support of a load of snow for the usual support by the human spine structure and substitutes downward leg motion for arm lifting motion to transfer the snow to a disposal area.

It is a still further object of the invention to provide a snow removal device that
20 can be constructed in various manners with single or multiple handle members and pivoting members.

It is a still further object of the invention to provide a snow removal device in which the snow can be either actively removed from the shovel blade by forcefully or
25 actively pivoting the blade to cause snow to be dropped therefrom or can be passively allowed to pivot down to eject snow therefrom.

It is a still further general object of the invention to provide a snow removal device which substitutes a sturdy physical support for support of a load of snow for or in
30 place of the spine or vertebral column of a snow shoveler plus substitutes the muscles

of the legs to lift such snow for or in place of the arms of the shoveler.

It is a still further object of the invention to provide a manually operated snow removal device which effectively substitutes support by the handle or principal support member of the snow removal device for support of the load by the vertebral column of the shoveler and the downward force of the shoveler's leg for lifting of the load by the arms of the shoveler.

It is a still further object of the invention to provide a snow shovel device incorporating a load support directly in contact with the ground during lifting of the load that serves as a handle for the shovel blade during collection of snow upon the blade.

It is a still further object of the invention to provide a mechanically aided handle mechanism or arrangement for a shovel blade which can be substituted for by a more conventional handle rendering the shovel blade usable as a conventional shovel as well as a mechanically aided shovel.

Still other objects and advantages of the invention will become clear upon review of the following detailed description in conjunction with the appended drawings.

SUMMARY OF THE INVENTION

An improved shovel type snow removal device is provided in which during lifting of the snow after a plowing motion during which snow is gathered on the shovel blade, 5 the shovel handle is supported upon the ground instead of on or by the spinal structure of the shoveler and lifting force upon the shovel blade is provided by downward leg force, supplemented preferably by a forward leg force, exerted upon a lever system to which the shovel blade is attached for manipulation. The device is formed from a more or less conventional shovel blade mounted upon a pivoting lever and preferably 10 provided with a second manipulating rod adapted to be forced forward by foot or leg pressure to tilt the blade in order to dump a load of snow from the blade or simply by partially unlocking the blade from the handle allowing it to downwardly rotate to dump snow accumulated upon it. By supporting the shovel on the end of its handle collecting snow and on the end of a lever when lifting snow and manipulating the shovel blade by 15 foot and leg action mediated by a lever system a user is enabled to clear an area of snow and deposit the cleared snow in a disposal area without placing any significant strain on the user's vertebral column or arms. The shoveling device of the invention may for sturdiness and balance be constructed with either multiple or single or unitary handle and lever systems.

BRIEF DESCRIPTION OF THE DRAWINGS

The following are drawings of several possible embodiments of the invention:

5 FIG. 1 is an isometric view from the upper right rear quadrant of a presently preferred embodiment of the snow shovel of the invention in plowing or collecting configuration.

10 FIG. 2 is an isometric view from the upper right forward quadrant of the embodiment shown in FIG. 1 in collecting configuration.

 FIG. 3 is a side elevation of the snow shovel or plow of the invention in plowing position, but with the blade unlocked.

15 FIG. 4 is a reduced scale isometric drawing of the snow shovel of the invention with the shovel blade locked and lifted to maximum lift height.

20 FIG. 5 is a side elevation of the snow shovel of the invention with the blade in the position shown in FIG. 4.

 FIG. 6 is a reduced scale isometric view of the snow shovel of the invention with the shovel blade unlocked and rotated into dumping position.

25 FIG. 7 is a side view with the blade of the shovel in the position shown in FIG. 6.

 FIG. 8 is a side elevation of an alternative embodiment of the invention as shown in the previous drawings in which further embodiment the handle of the shovel is curved to approximately a 45 degree angle at the bottom about the axis of the ground engaging wheel and the pivot lifting arm has a straight configuration.

30

FIG. 9 is a further side elevation of the embodiment shown in FIG. 8 with the handle elevated to a vertical position and the pivot lifting arm elevated to substantially maximum position.

5 FIG. 10 is a further side elevation of the embodiment shown in FIGS. 8 and 9 with the shovel blade unlocked and rotated partway downwardly.

FIG. 11 is a four part time lapse sequence of the embodiment of the invention shown in FIGS. 8, 9 and 10 in two initial plowing or scooping modes, a third elevated
10 mode and a fourth shovel blade dumping mode.

FIG. 12 is a lower view and FIG. 13 a side view of a preferred nonskid insert for placement in the lower ends of the handle section of the shovel of the invention and showing the hardened steel surface of such insert.

15

FIG. 14 is a disassembled or broken apart view and FIG. 15 is a manufacturing parts list keyed to the individual parts shown in FIG. 14 of the separate parts of the shovel of the invention ready for assembly.

20 FIG. 16 is a diagrammatic side view of an alternative embodiment of the invention making use of a push rod controlled by a foot pedal to control the position of and dump the shovel blade.

FIG. 17 is a diagrammatic side view of a still further embodiment of the invention
25 using a swing bar for control of a push rod by the foot of the user to control the position of and dump snow from the blade of the shovel.

FIG. 18 is an isometric view similar to FIG. 4 but showing the use of a separate push rod to control the attitude of the shovel blade.

30

FIG. 19 is an isometric view similar to FIG. 6 but with the blade pushed forward by the push rod to snow dumping position.

FIG. 20 is an isometric view of the rear of the shovel blade with fittings for use in
5 holding the blade to the handle via the pivoting lift or fulcrum rod plus upper fittings for attachment to a push rod as in FIG. 18 and 19.

FIG. 21 is a view of a separate handle that can be attached to the blade of FIG. 12 to form a regular or more conventional shovel.

10

FIG. 22 is an isometric left front quadrant view of the separate handle attached to the shovel blade of FIG. 12 to form an ordinary shovel as distinguished from the mechanical lift aided shovel of the invention.

15

FIG. 23 is an isometric right rear quadrant view of the separate handle attached to the shovel blade to form a conventional shovel as distinguished from the blade of the mechanical lift shovel of the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The following detailed description is of the best mode or modes of the invention presently contemplated. Such description is not intended to be understood in a limiting
5 sense, but to be an example of the invention presented solely for illustration thereof, and by reference to which in connection with the following description and the accompanying drawings one skilled in the art may be advised of the advantages and construction of the invention.

10 It is standard practice in the removal of congealed precipitation whether in the form of snow, sleet, hail or the like, the most prevalent form normally handled being snow, to either push or plow such congealed precipitation, or snow, from the location where it is not desired to a disposal location or alternatively to lift or shovel the snow from the place where it is not desired to a disposal location. While pushing or plowing
15 snow and the like generally places the least strain upon the person carrying out such pushing or plowing operation, accumulated snow in the disposal area quickly blocks further horizontal movement of such accumulated precipitation, particularly in the case of so called "wet snow," which quickly packs into a heavy semi-consolidated mass. Consequently, unless the snow is lifted and deposited on top of the previous
20 accumulation, placement of snow in the disposal area quickly reaches a substantial saturation point. On the other hand, if the snow is lifted by a shovel or the like, it can be consecutively placed upon the top of earlier accumulations considerably increasing the capacity of such disposal areas or locations. Shoveling or physically lifting snow and other similar accumulations and depositing it on top of previous accumulations means
25 not only that considerable stress is applied to the components of the third class lever system that makes up the arm and hand while grasping the handle of a shovel or the like and lifting, i.e. with the force or lifting effort positioned between the fulcrum constituted by the elbow and the weight grasped by the hand. Alternatively, the snow on the blade of a shovel may be lifted by the first class lever system constituted by the
30 hand grasping a midpoint of the shovel handle with the weight on the blade of the

shovel on one side of the hand and the force applied to the handle in a downward direction on the other side of the fulcrum constituted by the supporting hand, the leverage being whatever the differential in length of handle sections is on either side of the supporting hand. In most lifting of snow on a shovel, the lever system involved is in effect a double system in which one hand lifts at the fulcrum, i.e. a third class lever system and the other hand pushes down on the opposite end of the shovel at the handle, i.e. a first class lever system. As the weight becomes greater, or the muscles on the supporting arm become more tired, the third class lever lifting is allowed to decline and more effort is applied by means of the first class lever arrangement represented by the hand grasping the shovel handle at a midpoint and the opposite hand pushing down on the shovel handle at the opposite end from the shovel blade. Whatever the lever system being used, however, the entire weight of the snow is effectively upon the spinal column of the shoveler, plus concentrated on one side of the shoveler, tending not only to force the spinal column downwardly and compressing the discs between the vertebrae not only overall, but tending to compress the discs more on one side than on the other so that the tendency is for the spinal disc to tend to be squeezed or extruded out from between the discs towards the less compressed side. It is not at all rare in such circumstances for the disc to be either ruptured or displaced toward one side, or both, with frequently excruciating pain as the disc material presses against the nerves of the spinal column either generally or against nerves passing between vertebrae to the rest of the body. While the young supple body is frequently able to withstand these unequal or lopsided strains placed upon the vertebral column, as the human body ages it is able to withstand the intermittent stresses and strains of shoveling to a lesser and lesser degree, although dependent somewhat upon how healthy the individual tends to be, the earlier injuries such individual has sustained and what physical conditions he or she maintains from day to day. Not only is the weight of a shovel of snow distributed unevenly to the vertebral column of the shoveler, but in placing it in the intended deposit area the vertebral column is frequently subjected to a twisting motion as the body is swung to deposit the load to one side or the other.

The present inventor in considering the problems in shoveling snow has realized that what is needed is a snow removal or shoveling device that places a minimum stress not only upon the arms of the shoveler, but also upon the vertebral column of the shoveler. The inventor has, therefore, designed a snow removal device which first
5 directly supports the weight of a shovel-full of snow not on the vertebral column of the shoveler, but upon the handle of the shovel, which rests during the lifting phase of shoveling not upon or passing through the shoveler's vertebral column, but upon the ground or other support upon which the shoveler stands. Secondly, the weight of the snow on the end of the shovel is not lifted by the relatively weak arm muscles of the
10 shoveler, but instead by a downward or principally downward force of the leg muscles. The legs contain, in the normal human body, the largest muscles and are usually the portion of the skeletal-muscular system which is kept in best physical condition as the result of the necessary walking and support of the body which the legs carry out in those who are not disabled in some manner.

15

In addition, the removal of snow is designed in the present invention to be accomplished principally by a plowing motion which scrapes or pushes the shovel blade along the ground, piling up snow both in front of the blade and upon it, after which the snow may be lifted by a fulcrumed or pivoting movement, force being applied to the end
20 of the fulcrum or pivot arm by the foot and leg of the shoveler while the shovel itself is supported upon the ground or other support surface. While the shovel blade is pivoted upward by the action of the foot and leg, or one foot and leg of the shoveler, the stance of the shoveler is not unbalanced by the use of one leg to lift the snow on the shovel (by a downward movement of the leg which is the most powerful movement of the leg
25 because of the normal support functions of the leg) because the shoveler standing upon one leg is balanced by simultaneous resting of the shovel handle upon the ground.

If it is desired to move the shovel while supporting the end of the handle upon
30 the ground, the end of the handle is preferable supplied with slide means such as small

sled-type runners or more preferably by small wheels placed so that by adjusting the angles of the handle with respect to upright, it can be rested directly and essentially immovably upon the ground or can be adjusted in angle so that runners or slides or more preferably small wheels can be supported upon the ground or other support
5 surface enabling the entire shovel structure to be moved bodily along the surface.

The snow removal device or improved shovel apparatus of the invention can be constructed in various ways and in various embodiments. For example, the handle of the device, which handle may be curved to facilitate both placement upon the ground
10 for support and control while moving may be in single column form or multiple or plural column form. Likewise, the pivot or fulcrum arm or arms to which the blade is attached, which arms are pivotally attached to the handle, may be single or multiple. However, since the shovel blade is often desirably larger than a normal shovel blade, because it is preferably used primarily in a plow mode and when lifted can support larger loads of
15 snow because it is lifted by the legs rather than the relatively weaker arms, it is often preferred that the pivot or fulcrum arm also be of multiple member construction to provide better balance, it being relatively difficult to prevent a single pivot arm from twisting when supporting a large unbalanced load on a wide shovel blade. Various pivots and pivoting arrangements can be used and the shovel blade is preferably in the
20 form of the usual curved rectangular blade. In fact, in one embodiment of the invention, when desired by the owner, the shovel blade can be disconnected from the normal mechanical and support arm arrangement of the invention and connected to a more conventional handle for more conventional use.

25 In the preferred version of the snow removal apparatus of the invention, the shovel is not only provided with a pivot arm supporting the shovel blade, but the shovel blade is pivoted more or less centrally upon the end of the pivot arm in such a manner that the blade may be either held more or less rigidly upon the pivot arm or allowed to pivot from a more or less horizontal position to a vertical position or even more than a
30 vertical position to dump or discharge snow from the blade into a deposit area. In the

simplest version of such embodiment, the shovel blade is provided with a locking arrangement that holds it rigid on the pivot arm or arms when gathering snow or in shoveling or plowing mode, but is disconnectable or unlockable when the blade is brought over a snow deposit area, whereupon the blade is unlocked and because of its
5 pivot point will rotated into a vertical or more than vertical position and dump its snow from it into the deposit area, whereupon the shovel blade may be pushed or kicked up into a locked position again and moved to gather another load of snow.

In another version of the invention, the blade angle will be actively or positively
10 controlled by an angled push rod or control rod arrangement by which the foot of the user may be used simultaneously or consecutively to both pivot the blade upwardly to lift a load of snow, but also when desired to dump such accumulated snow from the blade to rotate the blade forwardly to dump the snow from it. In this version or embodiment of the invention, the push rod or angle control rod may be preferably
15 slidably attached to the handle and/or pivot rod by a sliding connection such as a slide groove in the angle control rod and/or in the handle. Such sliding connection must usually be a four way or multiple slide connection, i.e. it must not only slide forwardly and backwardly, but also up and down in any direction, because as the slide rod moves the geometry of the mechanical system continuously changes as movement occurs.
20 Alternatively, as shown, the push rod may be unsupported except at its two ends. A foot pedal or push rod arranged so that when the foot pedal is turned down or pivoted down, the push rod which is connected to an outer point of the pedal is pushed forwardly forcing the top of the blade forwardly and the entire blade into a more vertical position to dump snow from the blade. Spring means may be provided to return the
25 foot pedal and blade to normal position when the user's foot releases pressure upon the foot pedal.

In a further embodiment, a suspended foot contact bar may be provided for contact by the foot of the operator. Downward force by the foot of the operator upon
30 the foot bar will pivot the shovel blade upwardly and forward force by the foot will move

the push rod forward to move the top of the blade outwardly and dump snow from it. In a further embodiment of the invention, the shovel blade pivot rod will be pivoted up by downward pressure or force upon the inner end by the foot while a separate push rod may be used to push out the top of the blade and dump the snow. Such push rod may
5 be activated by the hand of the shoveler.

In each of the above instances or arrangements for dumping snow from the blade, once accumulated upon the blade, the weight of the snow or other congealed precipitation is supported by the end of the shovel blade handle resting upon the
10 ground, thus removing compressive stress normally upon the spine of the shoveler from the spine to the shovel handle, while the stress of actually lifting the shovel blade with a load of snow is provided by a downward force on one foot utilizing the strong muscles of the leg rather than the relatively weak muscles of the arms. The only stress upon the arms and spine of the user occurs during actual horizontal movement of the shovel with
15 a plowing action when the arms of the user partially support the handle of the shovel at an angle and force the shovel blade sidewise into the snow preparatory to movement to the disposal area partially supported by the arms, but mostly supported by small runners, skids, or wheels at the bottom of the handle. When the shovel reaches the disposal area the handle of the shovel is pivoted upwardly in position and the foot is
20 used to actually lift the snow. A relatively young vigorous shoveler may sometimes actually carry the shovel with a load of snow from the point being shoveled a short distance to the disposal area or possibly pivot his or her body to the disposal area while supporting the load. However, such shoveler then, after placing the lower end of the shovel handle firmly upon the ground surface, will apply downward movement of the
25 foot to the pivot arm to lift the snow and deposit it in the disposal area. In this way, while the arms and spine of the shoveler are stressed during carrying or movement of the load of snow to the disposal area, the more vigorous or stressful lifting of the load to deposit it upon other accumulated snow in the disposal area is avoided. In other instances, in the case of less vigorous shovelers for which the shovel is particularly
30 designed the snow load will never be placed upon or applied in compression to the

back, or spine, of the shoveler at all.

FIGS. 1 through 7 illustrate a first preferred embodiment of the invention, FIGS. 8 through 11 illustrate alternative embodiments, and FIGS. 12 through 15 illustrate another alternative embodiment that enables the shovel blade used in the invention to be converted to more traditional use. Referring to FIGS. 1 through 7, the numeral 10 generally represents the snow removal device of the invention. In its most basic form, device 10 is comprised of an elongated double support shaft 20, or handle, which serves as a combination handle and ground-engaging fulcrum, material handling blade or scoop 30, and foot activated lever or lifting mechanism 40.

Referring now to FIG. 1, in the presently described embodiment of the elongated support shaft 20 such shaft is bifurcated and as such is comprised of first and second shaft sections 21a and 21b, which sections are substantially mirror images of each another. Shaft 20 has an elongated upper shaft portion 22, a central portion 23, and a lower shaft portion 24. Upper shaft portion 22 is generally straight along its entire length, while central portion 23 is also straight but could be cambered downwardly somewhat towards the ground surface so that lower shaft portion 24 would be substantially perpendicular to such ground surface as shown in the embodiments depicted in FIGS. 8 and 9. Transverse handle grip members 25a and 25b are connected to the upper ends of shaft sections 21a and 21b, although alternatively and possibly preferably such handle grip members 25a and 25b are formed integrally with shaft 20. Handle grip members 25a and 25b are of course used to handle and maneuver the snow removal device 10 as described in more detail below. Shaft sections 21a and 21b are preferably tubular and made from a strong yet lightweight metal material such as aluminum. As shown in FIGS. 1, 4, and 6, lower portions 24 of first and second sections 21a and 21b curve outwardly and then downwardly so that a solid base for pivoting and lifting the shovel blade as described below results. Ground-engaging end pieces 27 preferably made from a non-skid material such as rubber may be attached to the ends of lower shaft portions 24 so that the device 10 does not slip

during lifting of the shovel blade **30**. When device **10** is in position for shoveling, end pieces **27** should be situated a few inches or fractions of an inch off the ground so that shaft **20** normally will not contact the ground and interrupt the pushing or shoveling movement but will glide supported on wheels **28**, which, as mentioned above, could be replaced by skids or runners. In addition, while shaft **20** is described above as being comprised of two sections **21a** and **21b**, it should be understood that shaft **20** could be comprised of a single shaft section. More rigidity with less weight will usually be obtained from use of a double or multiple construction, however.

10 The blade **30** used with the snow removal device **10** of the present invention is preferably molded out of a durable plastic such as PVS, although any other suitable material such as steel, or aluminum or an aluminum and/or magnesium alloy may also be used. Blade **30**, best shown in FIGS. **1** and **2**, is preferably generally rectangular in plane and slightly or somewhat curved in cross-section, and includes front and rear
15 sides **31** and **32**, top edge **33**, ground engaging lower edge **34**, and side edges **35**. Although blade **30** may be in various sizes, in one embodiment blade **30** has a width of approximately thirty-two inches and a height of approximately twenty-four inches. Lower edge **34** may also be slightly curved or concave if desired, and blade **30** may also have shallow or low side walls **35a** or be somewhat more cup or scoop-shaped to
20 prevent material from slipping off sides of the blade during filling or lifting of the blade as described below.

As shown particularly in FIGS. **1** and **7**, mounted on rear side **32** of blade **30** are pairs of frame pieces or bracket members **36-37** and **38-39** which pairs are spaced
25 horizontally centrally from one another. Bracket members **36-37** and **38-39** are preferably integrally molded with blade **30** if the blade is of a plastic composition, although they may also be separately secured such as by rivets or bolts or welding, particularly if the blade is metallic, and serve as receiving members for connecting blade **30** directly to lever mechanism **40** and ultimately to handle shaft **20**. In addition,
30 blade **30** should be separable from lever mechanism **40** so that it may be replaced if

necessary due to wear, or so that a slightly larger or smaller blade or a blade having a different curvature may be used if desired. As explained later, the blade **30** may also be separated from the mechanism of the invention and a conventional handle applied. The blade is secured to the pivot arm **40** by means of removable pivot or cotter pins

5 **39a.**

A preferred arrangement of lever mechanism **40** will now be described.

Essentially, lever mechanism **40** is comprised of a pair of closely spaced parallel lever arms **41** and **42**, a pair of outwardly splayed sections **45** and **46**, and foot stirrup **60**.

10 Parallel lever arms **41** and **42** having upper ends **43** and lower ends **44** extend between the two sections **21a** and **21b** of shaft **20**. The extreme lower ends **45** and **46** of lever arms **41** and **42** are preferably curved outwardly from shaft **20** and are pivotably connected to the rear side **32** of blade **30** in channel or bracket members **36** and **37** via pivot bolts or cotter pins **39a**. The side walls of bracket members **36** and **37** prevent
15 arms **41** and **42** from moving laterally with respect to blade **30**. Arms **41** and **42** are also pivotably secured to shaft **20** at pivot **51** so that, as explained below, the central section **23** of shaft **20** rotates about a fulcrum with pivot **51** serving as such fulcrum or pivot point for lever mechanism **40** used in raising or lifting blade **30**.

20 As shown best in FIGS. **4** and **6** foot engaging member or stirrup **60** serves as the actuating means for lever mechanism **40**. Stirrup **60** as shown is generally rectangular in shape with slightly inclined upper sides and has a lower foot contacting surface **61** and two side members **63a** and **63b** extending upwardly and then over or inwardly to pivotally connect to the pivot arm **40**. Stirrup **60** is shown in FIGS. **1**, **2**, and
25 **3** folded upwardly against the pivot arm **40** where it will normally be out of the way during plowing or collection of snow with blade **30**, while stirrup **60** is shown downwardly dependent in the position it will assume as the shovel is lifted and dumped from a raised position in FIGS. **4**, **5**, **6**, and **7**.

30 Stirrup **60** is provided with foot contact surface or lower end **61**, rearward or

upper end **62**, side surface **63**, and inclined pivot supports **64**. Upper ends **43** of arms **41** and **42** are pivotably connected to stirrup pedal **60** along upper end **64**, while the outer ends **47** of the two sections **45** and **46** of pivot arm **40** are pivotably connected preferably to brackets **37**.

5

The pivot arm **40** comprised of closely spaced arm sections **41** and **42** and diverging sections **45** and **46** is maintained ordinarily in downward position by gravity and will be maintained in any raised position assumed or to which it is brought by ratchet wheel mechanism **75**, which, however, can be released by operation of control
10 arm **77** through rod or cable linkage **79**. As a result of such ratchet linkage the blade **30** will normally rest upon the ground surface unless it is deliberately lifted at least one ratchet width by movement either of the pivot or fulcrum arm **40** or by riding over something on the ground which may lift the shovel blade at least one ratchet height. If it is desired to press the blade forcefully against the ground surface, the user can pull
15 upwardly upon the end of the pivot arm **40** while, if necessary, disengaging the ratchet mechanism by operating or pulling the ratchet release handle **77**. If the blade **30** is deliberately raised to lift a load of congealed precipitation, i.e. snow, the ratchet wheel mechanism will retain the blade at whatever position it is raised to. However, if it is desired to lower the pivot arm together with the shovel blade such as, for example, after
20 snow has been dumped from the shovel blade, operation of the ratchet control arm **77** will through linkage **79** in a conventional manner release the ratchet mechanism **75** and allow the blade **30** to return to ground level or wherever the operator wishes to position it.

25 The shovel blade **30** is pivoted at brackets **36** and **37** such that more of the blade and any load supported upon it will be positioned in front of or beyond the brackets than behind such brackets. Thus, if the blade is not locked in place by the locking mechanism **80** it will be overweighted and will rotate to a vertical position dumping any snow accumulated upon it. The locking arrangement **80** shown in outline comprises a
30 conventional spring loaded bifurcated rocking arm mechanism **81** having a first control

arm **81a** and a second locking arm **81b** (see in particular FIG. 7) which are pivoted together on a base pivot **83**. The bifurcated mechanism is pivoted on its base and spring biased toward the outer end of the pivot arm **40** so that the locking arm is normally interlocked through slot **81c** with a pin **81d** extending between bracket pieces **38** and **39** (see FIG. 1). So long as the rocker arm **81** is rocked forward with locking arm locked onto or over the pin **81d** the shovel blade will be retained in the position shown in FIGS. 1, 3 and 4. However, by operation of locking lever **85** on the left handle **25a** of the shovel a wire connection **87** between such lever and control arm **81a** will retract locking ratchet mechanism arm **81b** backward displacing the slot in locking arm **81b** from over pin **81d** and releasing blade **30** to rotate downwardly to dump any snow held upon such blade.

As previously generally described, operation of the snow removal device **10** to quickly clear snow, slush, or other granular or crystalline water material from a surface such as a sidewalk or driveway with a minimum amount of physical exertion and strain is more specifically as follows. The shovel or plow device **10** may be moved to the area to be cleaned by the user by pushing or pulling the device on wheels **28**, which as described could be substituted by suitable runners or slides. Once in position, bottom edge **34** of blade **30** is placed in contact with the ground surface to be cleared or shoveled. The user, standing behind handle grip members **25a-b**, grasps and pushes on such handles so that device **10** is moved forwardly in a plowing action with blade **30** in contact with the ground surface, causing snow and the like to be shoveled or transferred onto the front surface of the blade in the usual manner. An auxiliary wheel or pair of wheels may also be situated on the rear side of the blade to aid in moving the device across the ground surface, although this is not generally necessary. When sufficient frozen material has accumulated on blade **30**, the user may then release foot stirrup **60** by rotating it downwardly away from pivot rod **40** and the foot of the shoveler may be placed in the stirrup and pressed down to force down the pivot rod **40** on the near side of the handle **20** and raise the two sections **45** and **46** of such pivot rod on the forward side of the handle lifting the shovel blade **30** along with it.

At this point, once the shovel blade is at least partially lifted by downward force to the inside of the stirrup **60** by the foot of the shoveler, the ratchet wheel **75** mechanism will serve to retain whatever height of the blade is attained and desirable
5 and the shovel may be moved on its wheels **28** to the disposal area or, in other words, into disposal position, whether this be immediately adjacent to the removal zone or location or at a distance therefrom. Once committed to disposal, the shovel is moved to a position as close to the desired disposal position as possible and the shovel is preferably rocked forward so that the handle **20** is essentially vertical and supported
10 upon the ground engaging end pieces **27** with the wheels **28** slightly off the supporting surface. Normally the pivot arm **40** will then be lifted at least somewhat higher over the disposal area and the hand lever **85** will be operated causing the thin cable **87** to apply tension through cable **87** retract locking arm **81b** from locking pin **81d** allowing the shovel blade to rotate from the weight of the snow and its own weight into the position
15 shown in FIGS. **6** and **7** allowing the snow to slide off the shovel onto the disposal area. The shovel handle **20** may then be tilted again until the wheels **28** again rest on the ground and is thereupon moved back into shoveling position. When the ratchet lever **77** is operated the pivot rod is released allowing the shovel blade to rotate downwardly to reach the ground surface, the force of contact with which upon the lower edge of the
20 blade will rotate the bottom of the shovel blade upwardly re-engaging the locking pin **81d** with the locking lever **81c**. The shovel can then be moved forward again to collect additional snow and the cycle repeated.

The sides **35a** of the shovel blade aid in retaining snow on the blade until the
25 blade is rotated down to dump the snow. If the ground surface should be uneven the sides prevent the snow from sliding off the side of the blade due to slight tipping of the shovel.

As will be evident particularly in FIGS. **1**, **3** and **7** the pivot arm **40**, which may be
30 as shown best in FIG. **1** of multiple side by side member construction, and has a bent

configuration in which the upper sections **41** and **42** extends at a somewhat different angle from the lower sections **45** and **46**. Otherwise the central pivot point on the handle **20** would tend to be too low to allow the shovel blade to be efficiently lifted high enough to place snow on earlier piled snow. It may be desirable to include a small
5 handle, not shown, at the end of the pivot arms **41** and **42** for auxiliary control of the pivot arm in handling the shovel, the lifting force, however, still being applied by the foot of the user pressing down in the stirrup **60**.

FIGS. **8** through **15** illustrates an alternative and presently most preferred
10 embodiment of the invention. The preferred embodiment of FIGS. **8** through **15**, in which FIG. **15** is a construction parts list for such embodiment, is substantially similar to the somewhat less preferred embodiment shown in FIGS. **1** through **7** and the same reference numerals are used in the two sets of views (except for the construction part numbers in FIGS. **14** and **15**), except where differences in parts occur, in which case an
15 appropriate letter designation is applied to the appropriate reference designation in FIGS. **8** through **13** to distinguish from similar designations in the prior drawings of FIGS. **1** through **7**.

The principal difference between the embodiment in FIGS. **8** through **14** as
20 shown best in FIGS. **8** through **13** is a 45 degree curve at the bottom of the shovel handle so that the end of the handle bears directly upon the underlying surface when the handle is held at a 45 degree angle. The ground engaging or nonskid portion of insert **27a**, shown individually in FIGS. **12** and **13**, is held in the end of the shovel handle by a jam fit or other appropriate manner with the teeth **27b** exposed. The teeth
25 **27b** of ground engaging member **27a** are made from hardened steel or alloy steel with preferably a waffle pattern type sharpened surface **27b** providing nonslip or nonskid characteristics for secure engagement with the ground surface, concrete surfaces such as sidewalks and the like and even steel plates or bridging sometimes used on travel surfaces. Such nonskid characteristics are especially important in icy conditions where
30 the rubber or other similar ground contact member shown in the embodiment of FIGS. **1**

through 7 may not be sufficiently stable. The same sort of ground engaging member may be used with the embodiment of FIGS. 1 through 7. The other major difference between the preferred embodiment of FIGS. 8 through 13 from the previous figures is that the pivot arm 40a upon which the shovel blade 30 is mounted on one end with the stirrup 60a attached to the other end is straight throughout as is made possible by placing it lower on the shovel handle.

As more particularly shown in FIG. 8 and 10, a shovel user may begin shoveling or plowing of snow with the ground contacting insert 27a essentially flat on the ground surface and the wheel or wheels of the handle just off the ground. If it is desired to pass the shovel blade over the ground in a more nearly horizontal position or to rest the wheels 28 on the ground the handle 20a may be tipped back a little farther so the weight of the shovel and any snow held thereon rests on the said wheels 28 mounted on the bottom of the handle by wheel mounting bracket 67. When the shovel is brought opposite a disposal area the handle 20a may be brought to a more vertical orientation as shown in FIG. 9 and the foot of the operator placed in the stirrup 60a to raise the pivot arm 40a as shown. Unlocking upper portion of the shovel blade 30a from the pivot arm 40a will then allow the blade 30a to rotate as shown in FIG. 10, or even farther, dumping any snow accumulated on the blade from the blade. If the snow is wet and tends to adhere or stick to the blade 30a the handle 20a can be shaken or sharply rocked frontward and backward to shake or jar the snow from such blade. Since the full weight of the shovel and any accumulated snow is supported upon the end of the handle as shown in FIG. 10 there is little or no stress or weight applied to the back or vertebral column of the shoveler. The sequence of pushing or plowing snow followed by lifting it and then dumping the snow is shown in time lapse sequence form in FIG. 11 progressing from the lower left of the figure to the upper right of the figure. It will be noted that the first two time lapse positions of the series of time lapse representations of the shovel of the invention are very nearly the same, except that the shovel blade is slightly more extended in the second time lapse view. In both initial time lapse sequences it should be understood that if the shovel is being moved on the wheels 28

the shovel handle **20a** will be tipped or inclined to the rear sufficiently to cause the wheels **28** to contact or be supported by the ground surface.

FIGS. **12** and **13**, as indicated above, show in broken apart format and list the various component parts of the embodiment of the shovel shown in the FIGS. **8** through **11** with the Table of FIG. **13** listing such parts by sequential number and names of the construction parts. The reference numerals of the broken apart showing of FIG. **12** are the sequential numerals of the parts list of the Table of FIG. **13** and not the operational numerical representations of FIGS. **8** through **11** which conform, where similar, to the reference numerals of FIGS. **1** through **7** showing the first embodiment of the invention.

FIG. **16** is a diagrammatic side elevation of an alternative version of the invention in which instead of the use of a foot stirrup to lift the shovel blade by downward pivoting of the pivot rod, there is instead a foot pedal to which force is applied plus an additional push rod attached to the foot pedal so that when the foot pedal is physically rotated the push rod actively forces the top edge of the shovel blade out to dump snow from such blade rather than allowing the shovel blade to passively rotate itself from overbalancing.

As shown in FIG. **16**, a shovel device **20a** in accordance with the invention has in this case a curved handle member **21c** with ground contact end piece **27a** and wheel **28a** held on a wheel mount **67** attached to the lower portion of the curved handle **21c** which as may be seen is particularly curved in the central section **21ca** of such handle. A shovel blade **30a** is pivoted to the end of a pivot or fulcrum arm **40a** thereby establishing a base or fulcrum on which blade **30a** may be pivoted upwardly. Preferably there will be two fulcrum arms **40a** designated here as arms **41a** and **42a** preferably pivotably mounted on opposite sides of the handle **21c** or, if the handle is itself of double construction, the pivot arms **41a** and **42a** will be on the two handle sections. As shown in FIG. **8**, to lift blade **30a**, the user places his or her foot on the foot pedal **61** and applies an even downward force thereon, the force being applied mainly directly to the front section **61a** where the pivot arms **41a** and **42a** are rotatably

pivoted with it. As such force is applied, arm **41a** and **42a** will pivot on pivot point **48** with handle **21c**, with the upper ends of arms **41a** and **42a** pivoting downwardly and the lower ends of such arms pivoting upwardly so that blade **30a** is lifted off the ground surface. The loaded scoop or blade **30a** thus is lifted with only minimal exertion or

5 strain on the body of the user. In fact, the user's body weight on the foot pedal is all that is normally required to lift the load, and only minimal or no further stress is applied on the user's back, shoulders, or arm muscles and/or joints in contrast to what is typically experienced when manually lifting a loaded shovel blade or scoop. The user has therefore replaced a second and third grade lever system, i.e. the combination

10 body and regular shovel handle lifted by the arms, with a first grade lever having a fulcrum point between the load and the lever and operated by the strong muscles of the legs or one leg. In addition, rather than the load being supported by the vertebral column of the shoveler, the load is supported by the handle of the shovel.

15 As indicated above, once the blade with the load thereon has been lifted using the lever mechanism as just described, the entire weight of the load is supported on shaft **21c**, and is held in such raised position by the downward pressure exerted on foot pedal **61** by the user's foot and body weight. Now the load must be dumped or removed from the blade in a suitable dumping area. To accomplish this, while still

20 gripping the handle members **21c** the shovel blade may be pivoted forwardly by pressing downwardly on the rearward end of the foot pedal with the foot. As will be understood from FIG. **16**, this causes the rearward end **61b** of the foot pedal **61** to move downward so that it is substantially below the forward end. Moving it downwardly, however, also, as may be seen in FIG. **16** will effectively pivot or move rear end **61b**

25 forwardly with respect to the shovel as a whole. Pivoting the rearward end **61b** of the foot pedal **61** downwardly also causes push rod or rods **65** to slide or be pushed forwardly without substantially effecting the angle or height at which arms **41a** and **42a** hold the shovel blade. Downward movement of the rearward end of foot pedal **61** therefore causes push rod or rods **65** to slide forwardly. This in turn causing the top

30 edge **32a** of blade **30a** to be pushed forwardly and blade **30a** to tilt from a more

horizontal position to a more vertical position, thereby allowing the snow load to fall off of the blade. The length of the pivoting foot pedal and the extent to which it is rotated determines how far forward the top edge of the shovel blade **30a** is pushed forward. To further aid in dumping the load, at the same time the user may pivot shaft **20a** upwardly
5 and forwardly, and shake the device, with the lower end of shaft **20a** still in contact with the ground surface, which will tend to cause any adherent snow to be detached from the blade. Once all of the snow has been removed from the blade, the user may then return the blade to its lowered position simply by removing his or her foot from the foot pedal **61** and allowing the blade to naturally pivot downwardly on the pivot rods **41a** and
10 **42a**. The device is now ready to be used to pick up another load. It will be evident that the same sort of ratcheting mechanism may be used in the embodiment shown in FIG. **8** as in the previous figures to hold the pivot arm **40a** with the shovel blade **30a** in an elevated position.

15 While previous snow removal devices have utilized lever mechanisms to lift a shovel load to waist height, an important difference and advantage of the present inventor's arrangement is that the lower end of shaft or handle **20** also serves as the fulcrum or ground-engaging member, while in prior art manual shoveling devices the shaft is connected directly to the shovel with the lever connected only to the handle
20 shaft. The present inventor's arrangement allows the handle to remain more or less stationary and disposed at the same angle while collecting snow on the shovel blade after which the foot pedal is used to lift the loaded shovel blade, so that less bending and force on the arms and back is required. In addition, in prior art pivotable shoveling aids, the pivot point for pivoting the blade upwardly is in a position on the handle shaft
25 above the height of the shovel blade. In the present inventor's arrangement, however, the pivot point may be moved from a position generally above the shovel blade on the standard handle to a position an inch or two behind the shovel blade. Such lower pivot position spaced behind the shovel blade allows the lever mechanism, because of the effectively greater leverage, to be used to lift the shovel blade using a lesser downward
30 force than if the pivot point was above the blade on the handle shaft. In addition, a

more sturdy and stable base or fulcrum for pivoting the blade is provided. A novel arrangement for dumping snow off the shovel blade by further rotating the foot pedal is also provided.

5 In an alternative embodiment, the snow removal device of the invention may also include a means for locking the shovel blade in a raised position. As a result, once such lock is engaged, the user does not have to keep his or her foot on the foot pedal to maintain the shovel blade in a raised or substantially horizontal position. Another advantage is that the user may now more easily transport the loaded snow shoveling
10 device to a remote dumping location on wheels **28**. Such locking may be an automatic locking mechanism incorporated into pivot **48** arrangement as in FIGS. **1-2** in the form of a ratchet mechanism so that when the blade is pivoted or lifted upwardly and reaches a certain point or position, the lock will automatically engage and hold the blade in such position. Alternatively, a manual lock such as a push lock may be used.

15

FIG. **17** illustrates diagrammatically another alternative embodiment of the snow removal device of the invention similar to that shown in FIG. **8**. In such embodiment the structure of handle shaft **21c** and blade **30a** have not been changed, and blade **30a** is still secured to shaft **20** by support or pivot arms **41a** and **42a**. However, in such further
20 embodiment, foot pedal **61** of FIG. **8** has been replaced with bar or stirrup **102** extending between the upper ends of push rods or braces **45** and **46**, and arms **104** and **105** pivotably connected between the upper ends of support pivot arm **41** and support pivot arm **42** and brace **46**, respectively. A hook **108** is provided to hold the upper ends of support arms **41a** and **42a** in close proximity to handle shaft **21a** during
25 actual shoveling. It is then unhooked when the load of snow is to be lifted. As will be noted, the doubling of pivot arm members **41a** and **42a**, push rods **45** and **46** and pivot arms **104** and **105** are diagrammatically shown by broken line phantom representations.

In use, after the snow removal device **10** is used to gather a load on blade **30a**,
30 the user will exert a downward pressure on bar or stirrup **102**, which will cause blade **30**

to be lifted off the ground and into a generally horizontal position. Thereafter, forward pressure may be placed on stirrup **102**, causing brace or push rod members **45** and **46** to move forwardly and tilt blade **30a** outwardly so that the load on blade **30a** is released to a suitable dumping area. A locking means such as described above may also be
5 integrated into such embodiment to aid in holding the blade in a horizontal position so that once loaded it may be moved to a suitable dumping area without having to maintain a constant downward pressure on the stirrup bar. The presently described embodiment generally is operated in the same manner as the previously described embodiment.

10

FIGS. **18** and **19** illustrate another alternative embodiment similar to that shown in FIGS. **4** and **6** wherein the snow removal device has been modified to include an active rotation system, rather than a passive blade release means for allowing blade **30** to passively pivot forwardly on support arms **41** and **42** when unlocked. As illustrated,
15 an active independent push rod **110** for actively pushing the top of the blade outwardly can be used to cause it to dump its load of snow. The push rod **110** includes a hand grip or ring **111** to aid in operating such push rod and is pivotally connected to the upper portion of the shovel blade so that the angular disposition of such shovel blade can be controlled by said push rod **110** as may be seen in FIGS. **10** and **11**. The loaded
20 shovel blade is still lifted by foot pressure applied in the stirrup **61**.

FIGS. **20** through **23** show how the shovel blade **30** of the invention may, if desired, be removed from its regular handle and associated pivoting lifting arm and a regular or conventional shovel handle attached to such blade for use as a conventional
25 shovel in a conventional mode. In FIG. **20** there is shown a right rear quadrant isometric view of the shovel blade **30a** used in the embodiments of the invention shown in FIGS. **16** and **17**. It should be understood, however, that a conventional shovel handle supplied with appropriate attachment means could be used with the shovel blades shown in FIGS. **1** to **7** or in FIGS. **18** and **19**. In FIG. **20** the back of the shovel
30 blade is provided with brackets **125** and **126** in the form of modified channel members

having opposed flanges **125a**, **125b** and **126a**, **126b**. Two other smaller channel sections **128** and **129** are supplied on the top portion of the back of the shovel blade. These channel brackets **125a** and **126a** are normally used for movable connection of the pivot rods **41a** and **42a** which are secured by suitable pins to the brackets.

- 5 Likewise, the brackets **128** and **129** are normally secured by suitable pins to the push rods **65** and **66**. As shown in FIG. **13**, a handle **135** is provided with a split or bifurcated lower and **136** and **137** and openings in lower narrow sections **144** and **145** which are adapted to slide into the modified channel brackets **125** and **126** and be locked or held therein by pins **151** and **152**. A further curved rod **155** is adapted to slide through
10 opening **157** in bracket **158** on the front of the handle **135**.

As will be understood from reference to the FIGS., when it is desired to use the shovel blade in a conventional manner, it can be separated from the handle **20** or **20a** of the invention by removing the pins from the brackets on the shovel blade and
15 replacing such handle by the conventional handle as shown in FIGS. **13**, **14** and **15**. The conversion only takes a few moments and facilitates double duty for the shovel blade. The arrangement also allows the shovel blade, particularly when made from a plastic material which may wear over an extended period, to be easily and quickly replaced on the mechanical handle of the invention even though the use of a
20 conventional handle may not be desired.

As will be understood from the forgoing description and accompanying drawings the invention as described allows shoveling and movement of snow without applying any significant stress to the arms or spine of the shoveler enabling many persons who
25 could not otherwise effectively shovel snow to do so and significantly reducing the possibility of injury in doing so for large numbers of others.

While the present invention has been described at some length and with some particularity with respect to the several described embodiments, it is not intended that it
30 should be limited to any such particulars or embodiments or any particular embodiment,

but it is to be construed with references to the appended claims so as to provide the broadest possible interpretation of such claims in view of the prior art and, therefore, to effectively encompass the intended scope of the invention.